## Lead Renovation, Repair & Painting Practice Exam

- 1. EPA's Renovation, Repair and Painting Final Rule (40 CFR 745) requires that renovations conducted for compensation on targeted housing.
  - A. can be performed by anyone
  - B. can only be performed by the homeowner
  - C. must be performed by Certified Firms using Certified renovators
  - D. can only be performed by Abatement Contractors
- 2. Target Housing is
  - A. a home built specifically for the elderly
  - B. any zero bedroom dwelling or studio apartment
  - C. military barracks
  - D. homes built on or before December 31, 1977 where a child could reside
- 3. A child occupied facility is
  - A. a daycare center or school
  - B. a portion of a building visited by the same child under the age of six when combined annual visits are 60 hours
  - C. any building that a child under the age of six occupies for at least 2080 hours a year, in two consecutive years.
  - D. any building children reside
- 4. Minor repair and maintenance activities are exempt from the EPA's Rule if they
  - A. disturb less than 6 square feet of interior painted surfaces per room and less than 20 square feet on exterior work
  - B. include windows by replacement
  - C. disturb more than 10 square feet per room of interior painted surfaces or 60 square feet of exterior component
  - D. there are no exemptions
- 5. The "Opt-Out" provision of the RRP rule applies when the homeowner certifies in writing:
  - A. that the homeowner and their family reside in the home
  - B. there is no child under age 6 or pregnant female residing in the home
  - C. there is no "Opt-Out" provision
  - D. all of the above

- 6. What is a good indication that a house or housing unit may contain lead-based paint?
  - A. its location
  - B. age of the tenants
  - C. date of construction
  - D. none of the above
- 7. How does lead enter the body?
  - A. ingestion
  - B. inhalation
  - C. hand to mouth contact
  - D. all of the above
- 8. The best way to check for lead exposure in children and adults is to take samples of:
  - A. blood
  - B. urine
  - C. skin cells
  - D. lung tissue
- 9. Which of the following activities could create a high level of lead dust?
  - A. dry sanding of lead- based paint
  - B. dry scraping of lead-based paint
  - C. dry broom sweeping
  - D. all of the above
- 10. Lead abatement work can be done by:
  - A. construction workers as part of their regular duties
  - B. EPA trained or certified renovators
  - C. EPA trained or certified lead-abatement workers and supervisors
  - D. OSHA certified construction safety workers
- 11. Which of following procedures are considered good worksite preparations per EPA's Renovation, Repair and Painting Final Rule (40 CFR 745)?
  - A. Power washing loose paint
  - B. Restricting sidewalk access at front of home during exterior work
  - C. Placing plastic barriers to contain the work area
  - D. All of the above

- 12. Which of the following equipment is appropriate for use on remodeling and renovation projects where lead may be disturbed?
  - A. leaf blowers and fans
  - B. HEPA vacuum, specialized cleaning detergents, mops, and buckets
  - C. blow torch to burn off paint
  - D. shop vacuum for clean-up
- 13. Which of the following is/are not prohibited lead hazard control methods?
  - A. HEPA vacuum and wet methods
  - B. heat guns operating above 1,100 degrees f.
  - C. open flame burning
  - D. excessive dry scraping and sanding
- 14. Clean-up is done:
  - A. immediately before the supervisor arrives
  - B. only if the home owner request it
  - C. using wet methods and HEPA vacuums
  - D. only if you see dust
- 15. Safe work practices after lead-based paint has been disturbed includes storing waste debris in:
  - A. open dumpsters
  - B. thick plastics bags or sheeting, preferably 6 mil or equivalent
  - C. dump trucks
  - D. pick-up trucks and passenger vehicles
- 16. EPA Renovator record keeping requirements stipulate that the contractor maintain:
  - A. Project records for three years
  - B. Disclosure records relating to the distribution of the lead pamphlet
  - C. Documentation of compliance with the requirements of the Lead-Based Paint Renovation, Repair, and Painting Program
  - D. all of the above

- 17. Interior cleaning verification is the responsibility of:
  - A. the homeowner
  - B. the worker
  - C. the certified renovator
  - D. anyone at the worksite
- 18. Emergency renovations are:
  - A. unplanned activities done to prevent an immediate safety hazard or to prevent significant property damage
  - B. new exterior siding and windows
  - C. kitchen remodeling
  - D. new additions
- 19. Work practice requirements specific to interior renovations include:
  - A. removing or covering objects within the work area
  - B. closing windows and sealing ducts within the work area
  - C. covering floors with taped down plastic sheeting
  - D. all of the above
- 20. If the home owner request that the contractor test paint for lead the contractor must:
  - A. use an EPA recognized lead-based paint testing kit
  - B. use any testing kit available
  - C. advise them it's not required
  - D. none of the above
- 21. Containment is required by the RRP rule because it:
  - A. reduces the risk to you and the residents
  - B. facilitates efficient cleaning of the work area
  - C. keeps unauthorized individuals out of the work area
  - D. all of the above
- 22. Exterior containment includes:
  - A. opening windows near the worksite
  - B. blocking streets and driveways
  - C. vacating the adjacent dwellings
  - D. none of the above

- 23. HUD's lead regulations impact:
  - A. all housing
  - B. commercial property
  - C. federally funded targeted housing
  - D. apartment buildings only
- 24. When lead- based paint will be disturbed by renovation for more than a day the certified renovator should:
  - A. wait to clean at the end of the project
  - B. cover all debris on the ground with plastic
  - C. remove all debris and HEPA vacuum all horizontal surfaces within the worksite daily

25.

C

- D. complete a dry broom sweep of the area
- 25. Final interior cleaning verification procedure within the worksite includes:
  - A. carpeted floors and tabletops
  - B. counter tops and windowsills within the worksite
  - C. all horizontal surfaces within and 2 feet outside the work area
  - D. all of the above

12.

13.

В

Α

Answ	ers		
1.	С	14.	С
2.	D	15.	В
3.	В	16.	D
4.	Α	17.	С
5.	С	18.	Α
6.	С	19.	D
7.	D	20.	Α
8.	Α	21.	D
9.	D	22.	С
10.	С	23.	С
11.	С	24.	С
	_		